

TITLE OF THE INVENTION

COMMUNICATION TERMINAL APPARATUS

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the  
benefit of priority from the prior Japanese Patent  
Application No. 2000-373256, filed December 7, 2000,  
the entire contents of which are incorporated herein by  
reference.

BACKGROUND OF THE INVENTION

10 1. Field of the Invention

The present invention relates to a wired or  
wireless communication terminal apparatus including a  
display section provided with illumination means such  
as a backlight.

15 2. Description of the Related Art

As well known, a telephone connected to a public  
network by a cable, or a mobile radio terminal, such as  
a mobile phone, includes a display section provided  
with a backlight that enhances its visibility.

20 The backlight is designed to be automatically  
turned off to save power, if the apparatus is not  
operated for a predetermined period of time.

Recently, such telephones or mobile radio terminal  
apparatuses have come to be loaded with a function of  
25 sending/receiving E-mails and/or accessing Web sites on  
the Internet.

Also when using the function, the backlight is

09964466-092801

automatically turned off to thereby save power, if the user does not operate the apparatus for a predetermined time period. If, for example, a lot of time is required to receive information, the backlight will be turned off even while the function is being executed.

This being so, in a dark place, the user has to turn on the backlight so as to read the received information if it is in the OFF state. This is inconvenient for the user. Further, it is possible that the user turns on the backlight before information is completely received, which increases the consumption of power.

Moreover, in the conventional case, the backlight is automatically turned on if the user executes a predetermined operation. Accordingly, even in the daytime or in a bright place, the backlight may be unnecessarily turned on to thereby consume extra power.

#### BRIEF SUMMARY OF THE INVENTION

The present invention has been developed to solve the above-described problems, and aims to provide a communication terminal apparatus that is very convenient when receiving information and is free from unnecessary turn-on of its backlight, thereby saving power.

To satisfy the aim, according to a first aspect of the invention, there is provided a communication terminal apparatus capable of receiving information

09964466-092801

from a communication system network, comprising:  
receiving means for receiving information from the  
network; a display configured to display information;  
illumination means for illuminating the display; a  
5 detector configured to detect completion of information  
reception by the receiving means; display control means  
for causing the display to display information received  
by the receiving means, when the detector has detected  
the completion of the information reception; and a  
10 illumination controller configured to cause the  
illumination means to illuminate the display, when the  
detector has detected the completion of the information  
reception.

In the communication terminal apparatus  
15 constructed as above, the illumination means is  
controlled so as to illuminate the display means when  
reception of information from a network has been  
completed.

According to a second aspect of the invention,  
20 there is provided a communication terminal apparatus  
capable of receiving information from a communication  
system network, comprising: receiving means for  
receiving information from the network; a display  
configured to display information; illumination means  
25 for illuminating the display; illumination detecting  
means for detecting an intensity of illumination; a  
detector configured to detect completion of information

09964466-092804  
T08260-99449660

reception by the receiving means; display control means  
for causing the display to display information received  
by the receiving means, when the detector has detected  
the completion of the information reception; and a  
5 illumination controller configured to cause the  
illumination means to illuminate the display, when the  
detector has detected the completion of the information  
reception, and the intensity of illumination detected  
by the illumination detecting means is not more than a  
10 predetermined value.

In the communication terminal apparatus  
constructed as above, the illumination means is  
controlled so as to illuminate the display means, when  
reception of information from a network has been  
15 completed, and the ambient illumination is not more  
than a predetermined value.

According to a third aspect of the invention,  
there is provided a communication terminal apparatus  
capable of receiving information from a communication  
20 system network, comprising: receiving means for  
receiving information from the network; a display  
configured to display information; illumination means  
for illuminating the display; timer means for measuring  
time; a detector configured to detect completion of  
25 information reception by the receiving means; display  
control means for causing the display to display  
information received by the receiving means, when the

09964466-092801

detector has detected the completion of the information reception; and a illumination controller configured to cause the illumination means to illuminate the display, when the detector has detected the completion of the information reception, and a time point detected by the timer means falls within a predetermined time period.

In the communication terminal apparatus constructed as above, the illumination means is controlled so as to illuminate the display means, when reception of information from a network has been completed, and a time point detected by the timer means falls within a predetermined time period.

According to a fourth aspect of the invention, there is provided a communication terminal apparatus capable of receiving information from a communication system network, comprising: receiving means for receiving information from the network; a display configured to display information; illumination means for illuminating the display; display control means for causing the display to display information received by the receiving means; and a illumination controller configured to cause the illumination means to illuminate the display, when the display control means has started display of information on the display.

In the communication terminal apparatus constructed as above, the illumination means is

09064466-092801  
T08260"99449660

controlled so as to illuminate the display means when information received from a network is started to be displayed on the display means.

According to a fifth aspect of the invention,  
5 there is provided a communication terminal apparatus capable of receiving information from a communication system network, comprising: receiving means for receiving information from the network; a display configured to display information; illumination means  
10 for illuminating the display; illumination detecting means for detecting an intensity of illumination; display control means for causing the display to display information received by the receiving means, when the detector has detected the completion of the  
15 information reception; and a illumination controller configured to cause the illumination means to illuminate the display, when the display control means has started display of information on the display, and the intensity of illumination detected by the  
20 illumination detecting means is not more than a predetermined value.

In the communication terminal apparatus constructed as above, the illumination means is controlled so as to illuminate the display means, when  
25 information received from a network is started to be displayed on the display means, and the ambient illumination is not more than a predetermined value.

09564466-092801

According to a sixth aspect of the invention, there is provided a communication terminal apparatus capable of receiving information from a communication terminal apparatus capable of receiving information from a communication system network, comprising:

5 receiving means for receiving information from the network; a display configured to display information; illumination means for illuminating the display; timer means for measuring time; display control means for causing the display to display information received by

10 the receiving means; and a illumination controller configured to cause the illumination means to illuminate the display, when the display control means has started display of information on the display, and

15 a time point detected by the timer means falls within a predetermined time period.

In the communication terminal apparatus constructed as above, the illumination means is controlled so as to illuminate the display means, when

20 information received from a network is started to be displayed on the display means, and a time point detected by the timer means falls within a predetermined time period.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and

25

099646-09201  
FOB250-9949560

5           The accompanying drawings, which are incorporated  
in and constitute a part of the specification,  
illustrate embodiments of the invention, and together  
with the general description given above and the  
detailed description of the embodiments given below,  
10       serve to explain the principles of the invention.

FIG. 2 is a view illustrating information stored  
15 in a warning-operation setup table storage area that is  
incorporated in the communication terminal apparatus of  
FIG. 1;

FIG. 4 is a view illustrating example information displayed, when executing the process of FIG. 3, on a display section incorporated in the communication terminal apparatus of FIG. 1;

25           FIG. 5 is a view illustrating example information  
displayed, when executing the process of FIG. 3, on a  
display section incorporated in the communication



terminal apparatus of FIG. 1;

FIG. 6 is a view illustrating example information displayed, when executing the process of FIG. 3, on a display section incorporated in the communication terminal apparatus of FIG. 1; and

FIG. 7 is a flowchart useful in explaining the operation of the communication terminal apparatus executed when data has been completely received.

#### DETAILED DESCRIPTION OF THE INVENTION

An embodiment of the invention will be described with reference to the accompanying drawings.

FIG. 1 shows a communication terminal apparatus according to an embodiment of the invention. In this embodiment, a description will be given of a mobile radio terminal apparatus as an example, which is incorporated in a mobile phone system that executes radio communication to and from a base station connectable to a network, using the TDMA (Time Division Multiple Access) system.

The mobile radio terminal apparatus shown in FIG. 1 comprises a radio section 10 provided with an antenna 11, a modem section 20, a TDMA section 30, a call section 40 provided with a speaker 43 and a microphone 44 (M), an incoming call informing section 50, a memory section 60, a user interface section 70, a sensor 80 and a controller 100.

A radio frequency signal, sent via a radio call

09064466 "0922001  
T08250" 99149660

channel from the base station connected to a mobile communication network, is received by the antenna 11, and then input to a receiving section 13 via a high frequency switch (SW) 12, which are incorporated in the radio section 10.

The receiving section 13 mixes the received radio frequency signal with a local oscillation signal generated by a frequency synthesizer 14, thereby converting it into an intermediate frequency signal.

A local oscillation frequency generated from the frequency synthesizer 14 is controlled by the controller 100 in accordance with the radio channel frequency. The radio section 10 also includes a received-electric-field-intensity detector (RSSI) 16.

The received-electric-field-intensity detector 16 detects the electric field intensity (hereinafter referred to as "RSSI") of a radio frequency signal sent from the base station, and supplies the detected value to the controller 100.

A demodulator 21 incorporated in the modem section 20 receives the intermediate frequency signal output from the receiving section 13, and subjects the received signal to digital demodulation, thereby reproducing a digital call signal.

A TDMA decoding section 31 incorporated in the TDMA section 30 separates, under the control of the controller 100, the digital call signal into a

09964466 092801

plurality of digital call signals corresponding to respective time slots. That one of the thus-obtained digital call signals, which corresponds to the slot assigned to the communication terminal apparatus called,  
5 is input to the call section 40.

The call section 40 comprises an adaptive difference PCM trans coder (ADPCM TRANS CODER) 41 and a PCM codec (PCM CODEC) 42. The adaptive difference PCM trans coder 41 and the PCM codec 42 sequentially decode  
10 the digital call signal, thereby converting it into an analog call signal. The analog call signal is amplified by a call signal amplifier (not shown) and output from the speaker 43 in the form of sound.

On the other hand, a to-be-sent sound received by  
15 the microphone 44 is sequentially encoded by the PCM codec 42 and the adaptive difference PCM trans coder 41, thereby being converted into a digital call signal. The resultant digital signal is input to a TDMA encoding section 32.

The TDMA encoding section 32 inserts the digital call signal from the adaptive difference trans coder 41 into a time slot designed by the controller 100, and supplies it to a modulating section 22. The modulating section 22 subjects a carrier signal to digital  
20 modulation, using the digital call signal. The thus-modulated carrier signal is input to a sending section 15.

09064460 9949660

5  
10

15  
20

25

storage area 60a.

The informing-operation-setup-table storage area 60a is an area that stores information concerning setup conditions of the informing operation, which is  
5 executed when data sent from a network via the base station has been received by the communication terminal apparatus. Specifically, as shown in FIG. 2, the area 60 stores "ON/OFF" information indicative of whether or not the informing operation should be executed,  
10 information indicative of a condition (TIME CONDITION, OPTICAL CONDITION, NO CONDITION) for the informing operation, and information indicative of the time period of the informing operation, which is set if the time condition is selected.

15 The user interface section 70 includes a display section 71 and a key input section 72. The display section 71 is formed of an LCD (Liquid Crystal Display) equipped with a backlight 711. The user interface section 70 can display information based on data  
20 received from a network via the base station, and is used to show the user the state of the communication terminal apparatus itself (a calling state/a called state; a residual battery amount; a received signal intensity), dial data read from the memory section 60,  
25 text data such as E-mails, and image data, etc.

The key input section 72 includes a key pad, such as a ten-key pad, used to execute standard call

09064466-092801

functions related to signal sending/receiving operations, and a key (or keys) used to switch the incoming-call informing methods (audible sound generation/light emission/vibration/no informing operation), and a key (or keys) used to execute various types of setups or functions, such as code input for selecting an incoming call sound, an incoming call melody, etc. These keys can be used as character input keys when creating an E-mail.

The sensor 80 detects the illumination of the ambient light in the vicinity of the communication terminal apparatus, and outputs the detected illumination data (hereinafter referred to "illumination data") to the controller 100.

The controller 100 includes a main control section realized by, for example, a microcomputer, and controls the above-described elements. Specifically, the controller 100 provides a time measurement function, using a timer 100a, a control function of executing voice communication or sending/receiving E-mails, using the aforementioned TDMA system, and a control function of accessing Web sites using Web browser software.

The controller 100 also provides a control function of informing, when reception of an E-mail or browser data on a Web site from a network has been completed, the user of it by lighting the backlight 711 of the display section 71 or sounding the sounding

device 51.

Although FIG. 1 does not show it, the communication terminal apparatus also comprises a power section including a rechargeable battery that powers the above-described elements.

A description will now be given of the operation of the mobile radio terminal apparatus constructed as above. In the following description, only the operations related to the present invention will be described, while others, related to standard communication functions, will be omitted. These operations are executed under the control of the controller 100.

Referring first to the flowchart of FIG. 3, a description will be given of a process of setting, for example, informing operation conditions when data reception has been completed.

When the user has requested the setup of the informing operation conditions, using the key input section 72, the following process is started.

First, at step 3a, an image as shown in FIG. 4 is displayed on the display section 71, thereby waiting for the user to operate the key input section 72 and input information as to whether or not the informing operation, such as light-up control of the backlight 711 of the display section 71 or driving control of the sounding device 51, should be executed when data

reception has been completed. Then, the program proceeds to step 3b.

5 If there is a request for executing the informing operation, "1" is set in the column of "ON/OFF" in the informing-operation-setup-table storage area 60a shown in FIG. 2. If, on the other hand, there is a request for inhibiting the informing operation, "0" is set in the column.

10 At the step 3b, it is determined whether or not "1" is set in the "ON/OFF" column of the informing-operation-setup-table storage area 60a, i.e. whether or not it is set up that the information operation should be executed.

15 If the answer at the step 3b is YES (ON setup), the program proceeds to step 3c, whereas if the answer is NO (i.e. "0" is set so as to inhibit the informing operation; OFF setup), the program is terminated.

20 At the step 3c, an image as shown in FIG. 5 is displayed on the display section 71, thereby waiting for the user to operate the key input section 72 and input information as to in which condition the informing operation should be executed. Then, the program proceeds to step 3d.

25 If there is a request for ③ "TIME ZONE SETTING", i.e. "TIME CONDITION", "1" is set in the column of "time condition" and "0" is set in the other columns in the informing-operation-setup-table storage area 60a



shown in FIG. 2.

If there is a request for ② "OPTICAL SENSOR SENSING", i.e. "OPTICAL CONDITION", "1" is set in the column of "OPTICAL CONDITION" and "0" is set in the other columns in the informing-operation-setup-table storage area 60a shown in FIG. 2.

Further, if there is a request for ① "NO CONDITION", "1" is set in the column of "NO CONDITION" and "0" is set in the other columns in the informing-operation-setup-table storage area 60a shown in FIG. 2.

At the step 3d, it is determined whether or not "1" is set in the "TIME CONDITION" column of the informing-operation-setup-table storage area 60a. If "1" is set in the column, the program proceeds to step 3e, whereas if "0" is set in the column, the program is terminated.

At the step 3e, an image as shown in FIG. 6 is displayed on the display section 71, thereby waiting for the user to operate the key input section 72 and input information as to a time period in which the informing operation should be executed. The input time period is set in the "OPERATION TIME PERIOD" column of the informing-operation-setup-table storage area 60a, thereby terminating the program.

Referring then to the flowchart of FIG. 7, the operation executed when data reception has been completed will be described. When the controller 100

108260-9949660

has detected the completion of reception of data, such as an E-mail or browser data on a Web site from a network, it executes the operation shown in FIG. 7.

After the completion of data reception, the controller  
5 100 executes a display operation, as well as the above operation, thereby executing a display based on the received data.

First, at step 7a, it is determined whether or not  
"1" is set in the "ON/OFF" column of the informing-  
10 operation-setup-table storage area 60a, i.e. whether or not it is set up that the information operation should be executed.

If the answer at the step 3b is YES (ON setup), the program proceeds to step 7b, whereas if the answer  
15 is NO (OFF setup), the program is terminated without executing the informing operation.

At the step 7b, it is determined whether or not  
"1" is set in the "TIME CONDITION" column of the informing-operation-setup-table storage area 60a. If  
20 "1" is set in the column, the program proceeds to step 7c, whereas if "0" is set in the column, the program proceeds to step 7d.

At the step 7c, it is determined whether or not the present time point detected by the timer 100a falls  
25 within a time period set in the "OPERATION TIME PERIOD" column of the informing-operation-setup-table storage area 60a.

09964466-092801  
T08250-9949550

If the present time point falls within the set time period, the program proceeds to step 7f, whereas if it falls outside the set time period, the program is terminated without executing the informing operation.

5           At the step 7d, it is determined whether or not "1" is set in the "OPTICAL CONDITION" column of the informing-operation-setup-table storage area 60a. If "1" is set in the column, the program proceeds to step 7e, whereas if "0" is set in the column, the program  
10           proceeds to the step 7f.

          At the step 7e, it is determined whether or not the intensity of illumination indicated by illumination data obtained by the sensor 80 is not more than a predetermined value.

15           If the illumination intensity indicated by the illumination data from the sensor 80 is not more than the predetermined value, the program proceeds to the step 7f. If, on the other hand, it is more than the predetermined value, the program is terminated without  
20           the informing operation.

          At the step 7f, the backlight 711 of the display section 71 is turned on, and the sounding device 51 is driven to generate a sound, so as to inform the user that data reception has been completed, thereby  
25           terminating the program.

          As described above, in the communication terminal apparatus of the present invention, the backlight 711

09064466 092801

is automatically turned on when data reception has been completed to thereby enable the user to see the received data. Therefore, the user does not have to operate the terminal apparatus when data reception has been completed. Further, in this structure, the backlight 711 is not unnecessarily turned on. As a result, the communication terminal apparatus is very convenient for the user when receiving data, and requires less power.

Furthermore, if the user selects "TIME CONDITION" as the informing operation condition, they are informed of the completion of data reception, only in a necessary time period, by the turn-on of the backlight 711 of the display section 71 or the sounding operation of the sounding device 51. Thus, the communication terminal apparatus can be adjusted in accordance with the user's life style or circumstances in which they use the apparatus. As a result, unnecessary turn-on of the backlight 711 can be avoided.

Similarly, if the user selects "OPTICAL CONDITION" as the informing operation condition, they are informed of the completion of data reception by the turn-on of the backlight 711 or the sounding operation of the sounding device 51, only when the ambient illumination is at a low level and the backlight 711 should be turned on. Thus, the communication terminal apparatus can be adjusted in accordance with the circumstances in

which they use the apparatus. As a result, unnecessary turn-on of the backlight 711 can be avoided.

5 The present invention is not limited to the above-described embodiment. For example, although in the embodiment, the turn-on of the backlight 711 of the display section 71 and the sounding operation of the sounding device 51 are used as informing operations, the light emission of the luminous body 52 and the vibration of the vibrator 53 can be used as informing operations in place of the first-mentioned operations.

10 Moreover, although in the embodiment, the backlight 711 is automatically turned on upon completion of data reception, it may be designed to be automatically turned on under the control of the controller 100 at the start of display of data received.

15 Also in this type of control, the backlight 711 may be automatically turned on only if the illumination detected by the sensor 80 is not more than a predetermined value. Alternatively, such automatic turn-on of the backlight 711 may be performed only in a predetermined time period.

20 In addition, the turn-on of the backlight 711 of the display section 71 and the sounding operation of the sounding device 51 (or the aforementioned emission of the luminous body 52 and vibration of the vibrator 53) are not necessarily executed simultaneously, but may be selectively executed.

09061466-092801  
TOPSECRET

Although in the embodiment, the backlight 711 is used as means for illuminating the display section 71, a sidelight may be employed instead of the backlight.

5 It is a matter of course that the present invention can be modified in various manners without departing from its scope.

10 Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

09064466 092801